



# Swaypro™

**Weight Distributing Hitch**

## **Stop Sway Before it Starts**

- Prevents sway in all weather conditions
- Easy to use—no pins or clips
- Back up without disconnecting
- Quickly hook up and disconnect
- Limited lifetime warranty



# Select the Swaypro That Fits Your needs

## Standard Coupler or an Underslung Coupler?



Swaypro uses a *Standard Hitch Head* (BXW4011) fitting a *Standard Coupler* welded to the top of the trailer frame.



If the trailer has a coupler welded underneath the frame, replace the hitch head with the *Underslung Hitch Head* (BXW4012).

## Clamp-On or Bolt-On Rotating Latches?



For trailers without cross members or equipment blocking attachment of latches use the standard *Clamp-On Latches* (BXW4010).



Trailers with cross members or equipment blocking attachment of clamp-on latches use *Bolt-On Latches* (BXW4021).

## Swaypro™ Standard Hitch Shank 7 Hole Adjustment/9" Receiver Stinger



0" to 5" adjustment



Typical for: Minivans, 1/2 ton pickups, cars.

BXW0350	350 lb	BXW1000	1000 lb
BXW0550	550 lb	BXW1500	1500 lb
BXW0750	750 lb	BXW2000	2000 lb

## Swaypro™ S Series Hitch Shank 9 Hole Adjustment/9" Receiver Stinger



0" to 7-1/2" adjustment



Typical for: Large SUVs, 3/4 ton pickups.

BXW0350-S	350 lb	BXW1000-S	1000 lb
BXW0550-S	550 lb	BXW1500-S	1500 lb
BXW0750-S	750 lb		

## Swaypro™ 11 Hole Hitch Shank 11 Hole Adjustment/10" Receiver Stinger



0" to 10" adjustment



Typical for: Pickups & SUVs with lift kits, HD trucks

BXW0356	350 lb	BXW1006	1000 lb
BXW0556	550 lb	BXW1506	1500 lb
BXW0756	750 lb		



Toll-free 24/7 Customer Care  
800-228-9289

[blueox.com](http://blueox.com)

© Blue Ox One Mill Road, Industrial Park, PO Box. 430 Pender, Nebraska 68047