



BXH10131

Adjustable Ball Mount Installation Instructions

US Patent #8, 033, 563



Adjustable Ball Mount BXH10131

2" Receiver, 3-3/4" Drop/Rise, 10,000 lbs. GVWR / 1,000 lbs. tongue weight rated

2" Ball, 8,000 lbs. GVWR / 800 lbs. tongue weigh rated

2-5/16" Ball, 10,000 lbs. GVWR / 1,000 lbs. tongue weigh rated



WARNING

Do not exceed vehicle's towing capacity or receiver hitch capacity, whichever is less.
See your Vehicle Owner's Manual to determine Vehicle Tow Rating.

BXH10131

Adjustable Ball Mount Installation Instructions

Disclaimer

The rating of the Adjustable Ball Mount is intended to represent the capability of the product and in no way reflect the ratings or capacity of the towing system it is being used with. You, the consumer or operator, are strongly advised to learn the ratings of the various components of the towing system and never exceed the limits of the lowest rated component being used.

The Adjustable Ball Mount consists of two separate parts referred to as the Dual Flange Platform (DFP) and the Dual Flange Ball (DFB). The DFP (dual flange platform) is rated weight carrying up to 10,000 lbs. GVWR (gross vehicle weight rating) and up to 1,000 lbs. tongue weight.

The DFB (dual flange ball) is rated up to 10,000 lbs. GVWR/1000 lbs. tongue weight when using the 2-5/16" ball and 8,000 lbs. GVWR/800 lbs. tongue weight when using the 2" ball.

Installation Instructions

1. Install the platform into the 2" receiver hitch of your vehicle and secure it with the included silver hitch pin and clip. Always secure the hitch pin with a cotter pin unless a locking device is being used.
2. Determine which hitch ball size to be used is 2" or 2-5/16". Once the approximate height for the dual ball installation has been determined, mate the DFB (Dual Flange Ball) to the platform by inserting the supplied yellow pin through the hole that line up with the holes in the platform. Secure the pin with the included yellow clip.

Note: The supplied pins are specifically engineered for the Adjustable Ball Mount. If replacement pins are needed, they must be replaced with original factory pins.



Notes:

- Prior to towing, check to make sure that the pins are secured into place with cotter pins.
- Never hook up trailer safety chains to the Adjustable Ball Mount.



BXH10131
Adjustable Ball Mount
Installation Instructions

CUSTOMER SERVICE COMMITMENT

Blue Ox® is committed to providing you with exceptional customer care throughout your lifetime with our products. Our team is here to assist you with any questions you may have regarding the performance of your product. Simply call (402) 385-3051 and you can speak with our customer care team.

Additionally, please visit our website to see which rallies our Destination America team will be attending. For a nominal fee, our service technician will service your towing system to ensure it's in proper working condition. Also, as a commitment to our customers, should you visit our factory, you can stay at our full service Blue Ox® campground at no charge along with enjoying a factory tour.

Again, thank you for being our customer and for the confidence you have shown in the performance of our products. It is because of customers like you we enjoy the success we have today.



© 2013 Blue Ox
One Mill Road, Industrial Park
Pender, Nebraska 68047
Phone: (402) 385-3051
Fax: (402) 385-3360
www.blueox.com