




BXH14161

Adjustable Ball Mount Installation Instructions

US Patent #8, 033, 563, 20200031185



Adjustable Ball Mount BXH14161

2" Receiver, 6" Drop/ Rise, 14,000 lbs. GVWR / 1,400 lbs. tongue weight rated

2" Ball, 10,000 lbs. GVWR / 1,000 lbs. tongue weigh rated

2-5/16" Ball, 14,000 lbs. GVWR / 1,400 lbs. tongue weigh rated



WARNING

Do not exceed vehicle's towing capacity or receiver hitch capacity, whichever is less.
See your Vehicle Owner's Manual to determine Vehicle Tow Rating.

BXH14161
Adjustable Ball Mount
Installation Instructions

Disclaimer

The rating of the Adjustable Ball Mount is intended to represent the capability of the product and in no way reflect the ratings or capacity of the towing system it is being used with. You, the consumer or operator, are strongly advised to learn the ratings of the various components of the towing system and never exceed the limits of the lowest rated component being used.

The Adjustable Ball Mount consists of two separate parts referred to as the Dual Flange Platform (DFP) and the Dual Flange Ball (DFB). The DFP (dual flange platform) is rated weight carrying up to 14,000 lbs. GVWR (gross vehicle weight rating) and up to 1,400 lbs. tongue weight.

The DFB (dual flange ball) is rated up to 14,000 lbs. GVWR/1,400 lbs. tongue weight when using the 2-5/16" ball and 10,000 lbs. GVWR/1,000 lbs. tongue weight when using the 2" ball.

Installation Instructions

1. Install DFP (dual flange platform) into the 2" receiver hitch of your vehicle and secure it with the included bent hitch pin and clip. Always secure the hitch pin with a cotter pin unless a locking device is being used.
2. Determine which hitch ball size to be used is 2" or 2-5/16". Once the approximate height for the ball installation has been determined, mate the dual ball to the platform by inserting the supplied clevis pins through the holes that line up with the holes in the platform. Secure the pins with the included cotter pins. A patented pre-installed rubber bumper is installed in the dual ball to help prevent excessive rattles. During installation, some force may be required to push the dual ball in to position to allow the clevis pins to mate correctly.

Note: The supplied pins are specifically engineered for the Adjustable Ball Mount. If replacement pins are needed, they must be replaced with original factory pins.



continued on page 3

BXH14161
Adjustable Ball Mount
Installation Instructions

Notes:

- Prior to towing, check to make sure that the pins are secured into place with cotter pins.
- Never hook up trailer safety chains to the Adjustable Ball Mount.
- The function of the pre-installed rubber bumper is to reduce rattles only.



CUSTOMER SERVICE COMMITMENT

Blue Ox® is committed to providing you with exceptional customer care throughout your lifetime with our products. Our team is here to assist you with any questions you may have regarding the performance of your product. Simply call (402) 385-3051 and you can speak with our customer care team.

Additionally, please visit our website to see which rallies our Destination America team will be attending. For a nominal fee, our service technician will service your towing system to ensure it's in proper working condition. Also, as a commitment to our customers, should you visit our factory, you can stay at our full service Blue Ox® campground at no charge along with enjoying a factory tour.

Again, thank you for being our customer and for the confidence you have shown in the performance of our products. It is because of customers like you we enjoy the success we have today.

© 2013 Blue Ox
One Mill Road, Industrial Park
Pender, Nebraska 68047
Phone: (402) 385-3051
Fax: (402) 385-3360
www.blueox.com